

STUD BOY APPLICATION CHART ARCTIC CAT 2014

Snowmobile Information			Riding Style				Wearbars		
			Safety		Performance				
2014 Model	Lug Height	Track Length	Stud Length	Stud Quantity	Stud Length	Stud Quantity	Deuce	Round	Shaper
Bearcat 570 XT	1.375	20 x 154	1.500	108	1.500	135	CAT-D2264-(add size)	CAT-R2264-(add size)	CAT-S2264-(add size)
Bearcat Z1 XT / Z1 XT LTD	1.375	20 x 154	1.500	108	1.500	162	CAT-D2264-(add size)	CAT-R2264-(add size)	CAT-S2264-(add size)
Bearcat 570	1.250	15 x 151	1.375	120	1.375	150	CAT-D2264-(add size)	CAT-R2264-(add size)	CAT-S2264-(add size)
Bearcat Z1 XT GS	1.375	20 x 154	1.500	108	1.500	162	CAT-D2264-(add size)	CAT-R2264-(add size)	CAT-S2264-(add size)
F570 / F5	1.000	15 x 128	1.080	102	1.080	136	CAT-D2264-(add size)	CAT-R2264-(add size)	CAT-S2264-(add size)
M 8000	2.250	15 x 153 or 162	N/A	N/A	N/A	N/A	CAT-D2264-(add size)	CAT-R2264-(add size)	CAT-S2264-(add size)
M 8000 HCR	2.600	15 x 153	N/A	N/A	N/A	N/A	CAT-D2264-(add size)	CAT-R2264-(add size)	CAT-S2264-(add size)
M 8000 Sno Pro / Ltd/ Ltd ES	2.600	15 x 153 or 162	N/A	N/A	N/A	N/A	CAT-D2264-(add size)	CAT-R2264-(add size)	CAT-S2264-(add size)
M 9000 Turbo	2.250	15 x 153	N/A	N/A	N/A	N/A	CAT-D2264-(add size)	CAT-R2264-(add size)	CAT-S2264-(add size)
M 9000 Turbo HCR / SnoPro / Ltd	2.600	15 x 162	N/A	N/A	N/A	N/A	CAT-D2264-(add size)	CAT-R2264-(add size)	CAT-S2264-(add size)
Sno Pro 500	1.250	15 x 128	1.375	102	1.375	136	CAT-D2264-(add size)	CAT-R2264-(add size)	CAT-S2264-(add size)
Sno Pro 120	0.500	10 x 68	N/A	N/A	N/A	N/A	N/A	CAT-R2217-add size	N/A
T570	1.000	15 x 144	1.080	114	1.080	143	CAT-D2264-(add size)	CAT-R2264-(add size)	CAT-S2264-(add size)
T Z1 / TZ1 LXR	1.000	15 x 144	1.080	114	1.080	170	CAT-D2264-(add size)	CAT-R2264-(add size)	CAT-S2264-(add size)
TZ1 Turbo LXR	1.250	15 x 144	1.375	143	1.375	170	CAT-D2264-(add size)	CAT-R2264-(add size)	CAT-S2264-(add size)
XF 7000 LXR / Sno Pro / Ltd	1.250	15 x 137	1.375	144	1.375	192	CAT-D2264-(add size)	CAT-R2264-(add size)	CAT-S2264-(add size)
XF 7000 Cross Tour	1.352	15x 144	1.375	141	1.375	188	CAT-D2264-(add size)	CAT-R2264-(add size)	CAT-S2264-(add size)
XF 7000 Cross Country Sno Pro	1.600	15x144	1.625	120	1.625	144	CAT-D2264-(add size)	CAT-R2264-(add size)	CAT-S2264-(add size)
XF 8000 Crosstour	1.352	15 x 141	1.375	141	1.375	188	CAT-D2264-(add size)	CAT-R2264-(add size)	CAT-S2264-(add size)
XF 8000 Cross Country Sno Pro	1.600	15 x 141	1.625	141	1.625	188	CAT-D2264-(add size)	CAT-R2264-(add size)	CAT-S2264-(add size)
XF 8000 LXR / Sno Pro / Ltd.	1.250	15 x 137	1.375	144	1.375	192	CAT-D2264-(add size)	CAT-R2264-(add size)	CAT-S2264-(add size)
XF 8000 H.C.SnoPro / Ltd.	2.250	15 x 141	N/A	N/A	N/A	N/A	CAT-D2264-(add size)	CAT-R2264-(add size)	CAT-S2264-(add size)
XF 9000 Turbo LXR/ Sno Pro / Ltd	1.250	15 x 137	1.375	144	1.375	192	CAT-D2264-(add size)	CAT-R2264-(add size)	CAT-S2264-(add size)
XF 9000 Turbo Cross Tour	1.352	15 x 141	1.375	165	1.375	188	CAT-D2264-(add size)	CAT-R2264-(add size)	CAT-S2264-(add size)
XF 9000 Turbo Cross Country Sno Pro	1.600	15 x 141	1.625	165	1.625	188	CAT-D2264-(add size)	CAT-R2264-(add size)	CAT-S2264-(add size)
XF 9000 Turbo H.C Sno Pro / Ltd	2.250	15 x 141	N/A	N/A	N/A	N/A	CAT-D2264-(add size)	CAT-R2264-(add size)	CAT-S2264-(add size)
ZR 5000 LXR	1.000	15 x 129	1.080	136	1.187	158	CAT-D2264-(add size)	CAT-R2264-(add size)	CAT-S2264-(add size)
ZR 6000 E LTIGRE/ ES	1.250	15 x 129	1.375	158	1.375	180	CAT-D2264-(add size)	CAT-R2264-(add size)	CAT-S2264-(add size)
ZR 7000 LXR/ Sno Pro / Ltd	1.250	15 x 129	1.375	158	1.375	180	CAT-D2264-(add size)	CAT-R2264-(add size)	CAT-S2264-(add size)
ZR 8000 LXR / Sno Pro / Ltd / RR	1.250	15 x 129	1.375	158	1.375	180	CAT-D2264-(add size)	CAT-R2264-(add size)	CAT-S2264-(add size)
ZR 9000 LXR / Sno Pro / Ltd / RR	1.250	15 x 129	1.375	158	1.375	180	CAT-D2264-(add size)	CAT-R2264-(add size)	CAT-S2264-(add size)

*121" Tracks Have 48 Lugs /128" Tracks Have 51 Lugs/ 136" Tracks Have 54 Lugs / 141" Tracks Have 47 Lugs/144" Tracks Have 57 Lugs /156" Tracks Have 62 Lugs

Round bars -45 = 4.5", -60 = 6", -75 = 7.5" - Deuce Bars -45 = 4.5", -60 = 6", -90 = 9" - Shaper Bars -45 = 4.5", -60 = 6", -75 = 7.5", -90 = 9"

** PLEASE REMEMBER THAT "DEUCE" BARS ARE SOLD AS SINGLE BARS – NOT AS A PAIR

Liberty Products, Inc. recommends that tunnel and/or heat exchanger protection be installed in all snowmobiles when traction products are utilized. Even if your snowmobile is equipped with factory tunnel protection we suggest that you check for adequate clearance of traction products before you ride. Riding without performing a clearance check can result in serious damage to your snowmobile. Stud quantity and carbide length must be balanced for safe and proper handling. If you are not using studs do not install overly aggressive wearbars.