

STUD BOY APPLICATION CHART

YAMAHA 2014

Snowmobile Information			Riding Style				Wearbars		
			Safety		Performance				
2014 Model	Lug Height	Track Length	Stud Length	Stud Quantity	Stud Length	Stud Quantity	Deuce	Round	Shaper
Apex / Apex SE	1.250	15 x 128	1.375	153	1.375	179	N / A	YAM-R2524-(add size)	YAM-S2524-(add size)
Apex XTX	1.250	15 x 144	1.375	143	1.375	168/192	N / A	YAM-R2524-(add size)	YAM-S2524-(add size)
FX Nytro	1.250	15 x 120	1.375	126	1.375	168	N / A	YAM-R2524-(add size)	YAM-S2524-(add size)
FX Nytro MTX	2.250	15 x 153 or 162	N/A	N/A	N/A	N/A	YAM-D2226-(add size)	YAM-R2226-(add size)	YAM-S2226-(add size)
FX Nytro XTX 1.75	1.750	15 x 144	N/A	N/A	N/A	N/A	N / A	YAM-R2524-(add size)	YAM-S2524-(add size)
Phazer MTX	2.000	14 x 144	N/A	N/A	N/A	N/A	YAM-D2226-(add size)	YAM-R2226-(add size)	YAM-S2226-(add size)
Phazer RTX	1.000	14 x 121	1.080	96	1.080	120	N / A	YAM-R2524-(add size)	YAM-S2524-(add size)
Phazer XTX	1.500	14 X 144	1.625	143	1.625	168/192	N / A	YAM-R2524-(add size)	YAM-S2524-(add size)
RS Vector	1.250	15 x 121	1.375	144	1.375	168/192	N / A	YAM-R2524-(add size)	YAM-S2524-(add size)
RS Vector LTX	1.250	15 x 136	1.375	162	1.375	189/216	N / A	YAM-R2524-(add size)	YAM-S2524-(add size)
RS Venture	1.250	15 x 144	1.375	114	1.375	170	N / A	YAM-R2524-(add size)	YAM-S2524-(add size)
RS Venture GT	1.250	15 x 144	1.375	114	1.375	170	N / A	YAM-R2524-(add size)	YAM-S2524-(add size)
RS Venture TF	1.250	15 x 151	1.375	120	1.375	180	N / A	YAM-R2524-(add size)	YAM-S2524-(add size)
RS Viking Professional	1.250	20 x 156	1.375	124	1.375	186	YAM-D2226-(add size)	YAM-R2226-(add size)	YAM-S2226-(add size)
SRX 120	0.500	10 x 68	N/A	N/A	N/A	N/A	N / A	CAT-R2217- (add size)	N / A
SR Viper	1.250	15 X 129	1.375	158	1.375	180	CAT-D2264-(add size)	CAT-R2264-(add size)	CAT-S2264-(add size)
SR Viper LTX / LTX SE	1.250	15 x 137	1.375	144	1.375	192	CAT-D2264-(add size)	CAT-R2264-(add size)	CAT-S2264-(add size)
SR Viper RTX SE	1.250	15 x 129	1.375	135	1.375	180	CAT-D2264-(add size)	CAT-R2264-(add size)	CAT-S2264-(add size)
SR Viper XTX SE	1.600	15 x 141	1.625	141	1.625	188	CAT-D2264-(add size)	CAT-R2264-(add size)	CAT-S2264-(add size)
Venture MP	1.250	16 x 144	1.375	114	1.375	171	N / A	YAM-R2524-(add size)	YAM-S2524-(add size)

*121" Tracks Have 48 Lugs /128" Tracks Have 51 Lugs/ 136" Tracks Have 54 Lugs / 141" Tracks Have 47 Lugs/144" Tracks Have 57 Lugs /151" Tracks have 60 Lugs / 156" Tracks Have 62 Lugs

**** PLEASE REMEMBER THAT "DEUCE" BARS ARE SOLD AS SINGLE BARS – NOT AS A PAIR**

Round bars -40 = 4", -45 = 4.5", -60 = 6", -75 = 7.5", -90 = 9" - Deuce Bars -45 = 4.5", -60 = 6", -90 = 9" - Shaper Bars -45 = 4.5", -60 = 6", -75 = 7.5", -90 = 9"

TRACK AND STUD INFORMATION IN BOLD ARE TO IDENTIFY SINGLE PLY TRACKS THAT REQUIRE POWER POINT PLUS STUDS

Liberty Products, Inc. recommends that tunnel and/or heat exchanger protection be installed in all snowmobiles when traction products are utilized. Even if your snowmobile is equipped with factory tunnel protection we suggest that you check for adequate clearance of traction products before you ride. Riding without performing a clearance check can result in serious damage to your snowmobile. Stud quantity and carbide length must be balanced for safe and proper handling. If you are not using studs do not install overly aggressive wearbars.