



STUD BOY APPLICATION CHART SKI DOO 2016



Snowmobile Information			Riding Style				Wearbars		
			Safety		Performance				
2016 Model	Lug Height	Track Length	Stud Length	Stud Quantity	Stud Length	Stud Quantity	Deuce	Round	Shaper
Expedition SE / LE 600 HO / 900 ACE / 1200	1.250	20 x 154	1.375	108	1.375	162	DOO-D2410-(add size)	DOO-R2410-(add size)	DOO-S2410-(add size)
Expedition Sport 550F / 600 ACE / 900 ACE	1.500	16 x 154	1.625	108	1.625	162	DOO-D2410-(add size)	DOO-R2410-(add size)	DOO-S2410-(add size)
Expedition Xtreme 800 R	1.750	20 x 154	1.875	108	1.875	162	DOO-D2410-(add size)	DOO-R2410-(add size)	DOO-S2410-(add size)
Freeride 137	1.750 or 2.250	16 x 137	CALL	NA	CALL	NA	DOO-D2410-(add size)	DOO-R2410-(add size)	DOO-S2410-(add size)
Freeride 800 R 146/154	2.500	16 x 146, 154	NA	NA	NA	NA	DOO-D2410-(add size)	DOO-R2410-(add size)	DOO-S2410-(add size)
Grand Touring Sport 600 ACE	1.250	15x 137	1.375	96	1.375	144	DOO-D2410-(add size)	DOO-R2410-(add size)	DOO-S2410-(add size)
Grand Touring SE 1200	1.000	15 x 137	1.080	96	1.080	144	DOO-D2410-(add size)	DOO-R2410-(add size)	DOO-S2410-(add size)
MXZ Blizzard 600 HO / 800 R / 900ACE / 1200	1.250	15 x 129	1.375	90	1.375	136	DOO-D2410-(add size)	DOO-R2410-(add size)	DOO-S2410-(add size)
MXZ Sport 600 Carb / 600 ACE	1.250	15 x 120	1.375	84	1.375	126	DOO-D2410-(add size)	DOO-R2410-(add size)	DOO-S2410-(add size)
MXZ TNT 600 HO / 800R / 900ACE / 1200	1.250	15 x 120	1.375	84	1.375	126	DOO-D2410-(add size)	DOO-R2410-(add size)	DOO-S2410-(add size)
MXZ X-RS 600 HO / 800 R	1.250	15 x 129	1.375	90	1.375	136	DOO-D2410-(add size)	DOO-R2410-(add size)	DOO-S2410-(add size)
MXZ X 600HO / 800R / 1200	1.250	15 x 129	1.375	90	1.375	136	DOO-D2410-(add size)	DOO-R2410-(add size)	DOO-S2410-(add size)
Renegade Adrenaline 600 HO / 1200	1.250	15 X 137	1.375	96	1.375	144	DOO-D2410-(add size)	DOO-R2410-(add size)	DOO-S2410-(add size)
Renegade Adrenaline 800 R / 900 ACE	1.250	15 X 137	1.375	96	1.375	144	DOO-D2410-(add size)	DOO-R2410-(add size)	DOO-S2410-(add size)
Renegade BackCountry 600 HO / 800 R	1.600	16 x 146	1.625	102	1.625	153	DOO-D2410-(add size)	DOO-R2410-(add size)	DOO-S2410-(add size)
Renegade BackCountry X 800R	1.600 or 2.000	16 x 146	CALL	102	CALL	153	DOO-D2410-(add size)	DOO-R2410-(add size)	DOO-S2410-(add size)
Renegade Enduro	1.250	15 x 137	1.375	96	1.375	144	DOO-D2410-(add size)	DOO-R2410-(add size)	DOO-S2410-(add size)
Renegade Sport 600 Carb / 600 ACE	1.250	15 x 137	1.375	96	1.375	144	DOO-D2410-(add size)	DOO-R2410-(add size)	DOO-S2410-(add size)
Renegade X 600 HO / 800 R / 1200	1.250	15 X 137	1.375	96	1.375	144	DOO-D2410-(add size)	DOO-R2410-(add size)	DOO-S2410-(add size)
Renegade X-RS 800 R	1.500 or 1.600	15 x 137	1.625	96	1.625	144	DOO-D2410-(add size)	DOO-R2410-(add size)	DOO-S2410-(add size)
Skandic WT 550F / 600 HO / 600 & 900 ACE	1.500	20 x 154	1.625	108	1.625	162	DOO-D2410-(add size)	DOO-R2410-(add size)	DOO-S2410-(add size)
Skandic SWT 600 HO / 900 ACE	1.250	24 X 156	NA	NA	NA	NA	DOO-D2410-(add size)	DOO-R2410-(add size)	DOO-S2410-(add size)
Summit Burton 800 R	2.500	16 x 154	NA	NA	NA	NA	DOO-D2410-(add size)	DOO-R2410-(add size)	DOO-S2410-(add size)
Summit SP 600 HO / 800 R	2.500	16 x 146, 154, 163	NA	NA	NA	NA	DOO-D2410-(add size)	DOO-R2410-(add size)	DOO-S2410-(add size)
Summit SP with T3 package	3.000	16 x 154, 163	NA	NA	NA	NA	DOO-D2410-(add size)	DOO-R2410-(add size)	DOO-S2410-(add size)
Summit Sport	2.250	16 x 154	NA	NA	NA	NA	DOO-D2410-(add size)	DOO-R2410-(add size)	DOO-S2410-(add size)
Summit X with T3 package	3.000	16 x 154, 163, 174	NA	NA	NA	NA	DOO-D2410-(add size)	DOO-R2410-(add size)	DOO-S2410-(add size)
Tundra LT 550F / 600 ACE	1.500	16 x 154	1.625	62	1.625	122	DOO-D2410-(add size)	DOO-R2410-(add size)	DOO-S2410-(add size)
Tundra Sport 550F / 600 ACE	1.250	16 x 137	1.375	96	1.375	144	DOO-D2410-(add size)	DOO-R2410-(add size)	DOO-S2410-(add size)
Tundra Xtreme 600 HO	2.500	16 x 154	NA	NA	NA	NA	DOO-D2410-(add size)	DOO-R2410-(add size)	DOO-S2410-(add size)

29"= 45 Lugs / 137"= 48 Lugs /146"= 51 Lugs /154"= 54 Lugs

Round bars -45 = 4.5", -60 = 6", -75 = 7.5" - Deuce Bars -45 = 4.5", -60 = 6", -90 = 9" - Shaper Bars -45 = 4.5", -60 = 6", -75 = 7.5", -90 = 9"

AT "DEUCE" BARS ARE SOLD AS SINGLE BARS – NOT AS A PAIR

For protection be installed in all snowmobiles when traction products are utilized. Even if your snowmobile is or adequate clearance of traction products before you ride. Riding without performing a clearance check can injury and carbide length must be balanced for safe and proper handling. Do not install overly aggressive wearbars.

TRACK AND STUD INFORMATION IN BOLD REPRESENT SINGLE PLY TRACKS WHICH REQUIRE POWER POINT PLUS STUDS