STUD BOY APPLICATION CHART
YAMAHA 2023

***WE RECOMMEND TO REMOVE THE QUIET LUG WHEN UNDER A STUD HEAD FOR THE BEST INSTALLATION**

Riding Style

Snowmobile Information			Safety		Performance		Wearbars		
2023 Model	**Lug**	**Track**	**Stud**	**Stud**	**Stud**	**Stud**	**Deuce**	**Round**	**Shaper**
Mountain Max LE	3.000	15 x 154/65	N/A	N/A	N/A	N/A	N/A	YAM-R2566-(add size)	N/A
Sidewinder LTX GT EPS	1.250	15 x 137	1.375	144	1.375	192	CAT-D2264-(add size)	CAT-R2264-(add size)	CAT-S2264-(add size)
Sidewinder LTX LE EPS	1.250	15 x 137	1.375	144	1.375	192	CAT-D2264-(add size)	CAT-R2264-(add size)	CAT-S2264-(add size)
Sidewinder LTX SE	1.250	15 x 137	1.375	144	1.375	192	CAT-D2264-(add size)	CAT-R2264-(add size)	CAT-S2264-(add size)
Sidewinder SRX LE EPS	1.000	15 X 137	1.080	144	1.187	192	CAT-D2264-(add size)	CAT-R2264-(add size)	CAT-S2264-(add size)
Sidewinder STX GT EPS	1.250	15 x 146	1.375	153	1.375	204	CAT-D2264-(add size)	CAT-R2264-(add size)	CAT-S2264-(add size)
Sidewinder XTX LE 146	1.600	15 x 146	1.625	153	1.625	204	CAT-D2264-(add size)	CAT-R2264-(add size)	CAT-S2264-(add size)
Sidewinder XTX SE 146	2.000	15 x 146	N/A	N/A	N/A	N/A	N/A	YAM-R2566-(add size)	N/A
SnoScoot ES	1.000	10 x 93	N/A	N/A	N/A	N/A	N/A	N/A	N/A
SR Viper LTX GT	1.250	15 x 137	1.375	96	1.375	144	CAT-D2264-(add size)	CAT-R2264-(add size)	CAT-S2264-(add size)
SRX 120 R	0.750	10 x 67	N/A	N/A	N/A	N/A	N/A	CAT-R2565-(add size)	CAT-S2565-(add size)
SX Venom	1.000	14 x 121	1.080	96	1.187	96	CAT-D2264-(add size)	CAT-R2264-(add size)	CAT-S2264-(add size)
SX Venom Mtn.	2.000	15 x 146	N/A	N/A	N/A	N/A	N/A	YAM-R2566-(add size)	N/A
Transporter 800	2.250	15 x 153	N/A	N/A	N/A	N/A	N/A	YAM-R2566-(add size)	N/A
Transporter Lite / 2 UP	1.600	15 x 146	1.625	102	1.625	102	N/A	YAM-R2566-(add size)	N/A

121" Tracks = 48 Lugs /129" Tracks = 45 Lugs/ 137" Tracks= 48 Lugs / 141" Tracks = 47 Lugs/144" Tracks = 57 Lugs /146" Tracks =51 Lugs /151" Tracks = 60 Lugs / 153" Tracks= Lugs/ 154" Track= Lugs/ 162" Track = Lugs

Round bars -40 = 4",-45 = 4.5", -60 = 6", -75 = 7.5", -90 = 9" - Deuce Bars -45 = 4.5", -60 = 6", -90 = 9" - Shaper Bars -45 = 4.5", -60 = 6", -75 = 7.5", -90 = 9"

TRACK AND STUD INFORMATION IN BOLD ARE TO IDENTIFY SINGLE PLY TRACKS THAT REQUIRE POWER POINT PLUS STUDS

Liberty Products, Inc. recommends that tunnel and/or heat exchanger protection be installed in all snowmobiles when traction products are utilized. Even if your snowmobile is equipped with factory tunnel protection we suggest that you check for adequate clearance of traction products before you ride. Riding without performing a clearance check can result in serious damage to your snowmobile. Stud quantity and carbide length must be balanced for safe and proper handling. If you are not using studs do not install overly aggressive wearbars.

** PLEASE REMEMBER THAT "DEUCE" BARS ARE SOLD AS SINGLE BARS – NOT AS A PAIR